

4~20mA迴路電源式顯示電錶 (無電源式) (24X48mm)
(4~20mA LOOP-POWERED,5 DIGITAL PROCESS MONITORS,24x48mm)

**MODEL
MA24-LL**



特點(FEATURES)

精確度0.05%滿刻度 ± 1 位數(Accuracy 0.05% F.S. ± 1 digit)
 顯示範圍-19999~99999可任意規劃(Programmable rate -19999 to 99999 digit)
 可直接量測直流4至20mA電流,無需另接輔助電源(Self-power,no external supply required)
 尺寸小(24x48x50mm),穩定性高(Dimension small (24x48x50mm) and High stability)
 分離式端子,配線容易(Discrote terminal,connector easy)
 CE 認證(CE EMC certification)

1.MODEL:MA24-LL

(選購型號)

2.SPECIFICATION (主要規格)

Aux.power supply : None
 (輔助電源)
 Measuring accuracy : 0.05% F.S. ± 1 digit(DC)
 (精確度) (23 ± 5)
 Input impedance : approx. 250 ohm with 20mA input
 (輸入阻抗)
 Input voltage drop : max. DC5V with 20mA input
 (輸入電壓降)
 Maximun input over : < ± 50 mA
 (最大過載能力)
 Sampling time : 2.5 cycles/sec.
 (取樣時間)
 Readout range : -19999 - 99999 digit adjustable
 (顯示值範圍)
 Zero (offset) range : -999~999 digit adjustable
 (歸零調整範圍)
 Span(scale) range : -999~999 digit adjustable
 (最大值調整範圍)
 Over input indication : " doFL " or "-doFL"
 (過載顯示)
 Polarity display : " - " for negative readings
 (極性顯示)
 Display : Brigh Red LEDs high 8.6mm(.338")
 (顯示幕)
 Temp. coefficient : 50ppm/ (0-50)
 (溫度係數)
 Parameter setting : Touch switches
 (參數設定方式)
 Memory mode : Non-volatile E² PROM memory
 (記憶型式)
 Case material : ABS
 (外殼材料)
 Dielectric strength : 2KVac/1 min. (input/case)
 (絕緣耐壓能力)
 Operating condition : 0-50 (20 to 90% RH non-condensed)
 (使用環境條件)
 Storage condition : 0-70 (20 to 90% RH non-condensed)
 (存放環境條件)
 Outside dimension : 24x48x50mm
 (外型尺寸)
 CE EMC Certification : EN 55022:1998/A1:2000 Class A
 (CE認證) EN 61000-3-2:2000
 EN 61000-3-3:1995/A1:2001
 EN 55024:1998/A1:2001

3.OUTSIDE DIMENSION AND CONNECTION DIAGRAM

(外型尺寸與開孔尺寸與配線圖)

