## **MOOG Flow Control Valves with Analog Interface**

## Without Integrated Electronics

	• Rated Flow: 3.8, 9.6, 19, 38 and 62 l/min. (1, 2.5, 5, 10 & 16.5 gpm) ∆p 70
- M	bar (1000 psi)
	<ul> <li>Rated Pressure: 310 bar (4,500 psi)</li> </ul>
Barren B	<ul> <li>Rated Signal: +/- 7.5, 20 and 100 mA series</li> </ul>
	<ul> <li>Port Pattern: ISO 10372 - 04 - 04 - 0 - 92</li> </ul>
G770 Series Flo	ow Control Valve
	• Rated Flow: 1.9, 3.8, 9.6, and 19 l/min. (0.5, 1, 2.5, and 5 gpm) ∆p 70
The second	bar (1000 psi)
	Rated Pressure: 210 bar (3,000 psi)
	• Rated Signal: +/- 4.0, 7.5, 15, 20 and 100 mA series
$\overline{}$	Port Pattern: Multiple options available
G631 Series Flo	w Control Valve
	• Rated Flow: 3.8, 9.6, 19, 38, 57, and 76 l/min. (1, 2.5, 5, 10, 15 and 20 gpm
	u∆p 70 bar (1000 psi)
	Rated Pressure: 310 bar (4,500 psi)
	Rated Signal: +/-50 mA series
	• Port Pattern: ISO 4401-05-05-0-94
72 Series Flow	Control Valve
	<ul> <li>Rated Flow: 100 l/min (25 gpm) to 227 l/min (60 gpm) ∆p 70 bar (1000 ps</li> <li>Bort Battern: ISO 10272, 06, 05, 0, 02</li> </ul>
	<ul> <li>Port Pattern: ISO 10372 - 06 - 05 -0 - 92</li> <li>Stop Posponso: 16 40 ms</li> </ul>
	Step Response: 16-40 ms

78 Series Flow C	ontrol Valve
	<ul> <li>Rated Flow: 76, 96, 114 and 151 l/min. (20, 25, 30, and 40 gpm) ∆p 70 bar (1000 psi)</li> <li>Rated Pressure: 210 bar (3,000 psi)</li> <li>Rated Signal: +/- 4.0, 7.5, 20 and 100 mA series</li> <li>Port Pattern: non-standard</li> </ul>
760 Series Flow	Control Valve
	<ul> <li>Rated Flow: 0.5, 1.9, 3.8, 9.6, 19, 38 and 57 l/min. (0.13, 0.5, 1, 2.5, 5, 10 &amp; 15 gpm) ∆p 70 bar (1000 psi)</li> <li>Rated Pressure: 210 bar (3,000 psi) normal   350 BAR (5,000 psi) special order</li> <li>Rated Signal: +/- 4, 7.5, 15, 20, 25 and 100 mA series</li> <li>Port Pattern: ISO 10372 - 04 - 04 0 - 92</li> </ul>
79-100 and 79-2	00 Series Flow Control Valve
	<ul> <li>Rated Flow: 114, 151, 246, 380 644, 795 and 100 l/min. (30,40,65,100,170,210 &amp; 270 gpm) ∆p 70 bar (1000 psi)</li> <li>Rated Pressure: 210, 310, &amp; 350 bar (3,000, 4,500, &amp; 5,000 psi)</li> <li>Rated Signal: "+/-15 and 40 mA series</li> <li>Port Pattern: -079-2xx &amp; 792: PORTS: 3.12 X 2.25, 8 BOLT PATTERN: 4.62 X 4.36OUT X 1.88IN \\ -079:ISO#10372-06-05-0-92</li> </ul>
Jet Pipe Flow Co	ntrol Valves
	<ul> <li>Rated Flow: 96, 114, 151 &amp; 227 l/min. (25, 30, 40 and 60 gpm) ∆p 70 bar (1000 psi)</li> <li>Rated Pressure: 210 bar (3,000 psi) normal 350 bar (5,000 psi) special order</li> <li>Rated Signal: +/- 5, 10, 20, 25 and 50 mA series</li> <li>Mounting Pattern: non-standard</li> </ul>