

The flame retardant cotton paper double-sided adhesive tape is made of high tensile white flame retardant cotton paper as the substrate, coated with environmentally friendly flame retardant acrylic adhesive on both sides, and isolated with blank double-sided release paper; Good flame retardant effect, balanced adhesion and holding force, excellent weather resistance, and wide application range.

Thickness: $110 \pm 5 \mu\text{m}$

Specification: 1020mm * 50m/100m, or according to customer requirements

Application:

The application of adhesive and fixed flame retardant materials in industries such as electronics and electrical appliances, such as batteries, sound-absorbing foam, film switches, Mylar sheets, etc.

Testing methods for typical test values of inspection project units

Suggestions for storage, transportation, and use:

Store in a dry and clean warehouse with a temperature of 5 °C -30 °C and a storage period of one year. Avoid mixing and transporting with organic solvents and sharp objects, and do not roll or throw them.

Based on the properties of pressure sensitive adhesive tape, we sincerely recommend:

- 1) The recommended usage conditions for adhesive tapes are 20-35 °C and 30-60% RH;
- 2) Before pasting, please confirm that the surface of the adhesive is clean and dry;
- 3) To fully utilize the adhesive tape, it is recommended to first stick it at one end and apply a pressure of over 1.5kg/cm² to the other end, provided that the material being adhered allows.