

辉达新能源-玉柴国 III T3 系列柴油发电机组技术参数表

机组型号	机组功率 kw	柴油机型号	燃油消耗 g/kw·h	发动机 功率 (KW)	缸数	缸径 (mm)	行程 (mm)	排量 (L)	压缩比	噪声 dB (A)	机组重 量(kg)	外形尺寸 (长*宽*高) (mm)
HDYC230	230	YC6MK350-D30	195	259/235	6	123	145	10.34	15:1	105	2500	3050×1150×1800
HDYC280	280	YC6MK420-D30	195	309/281	6	123	145	10.34	15:1	105	2500	3050×1150×1800
HDYC300	300	YC6MK450-D30	195	331/301	6	123	145	10.34	15:1	105	2500	3050×1150×1800
HDYC330	330	YC6MJ500-D30	195	370/335	6	123	145	10.34	15:1	105	2500	3050×1150×1800
HDYC360	360	YC6MJ540-D30	195	402/365	6	123	145	10.34	15:1	105	2500	3050×1150×1800
HDYC400	400	YC6MJ600-D30	195	441/400	6	123	145	10.34	15:1	105	2500	3050×1150×1800
HDYC330	330	YC6K500-D31	195	370/335	6	129	155	12.15	15:1	110	2550	3050×1150×1800
HDYC330	330	YC6K500-D30	195	370/335	6	129	155	12.15	15:1	110	2550	3050×1150×1800
HDYC360	350	YC6K520-D30	195	382/356	6	129	155	12.15	15:1	110	2550	3050×1150×1800
HDYC400	400	YC6K600-D30	200	441/401	6	129	155	12.16	14.5: 1	110	2600	3150×1200×1880
HDYC440	440	YC6T660-D31	220	485/441	6	145	165	16.35	15:1	116	3850	3300×1200×2000
HDYC520	520	YC6T780-D31	220	572/520	6	145	165	16.35	15:1	116	4000	3200×1200×2050
HDYC560	560	YC6TD840-D31	220	616/561	6	152	180	19.59	15.1	115	4600	3500×1250×2100
HDYC600	600	YC6TD900-D31	195	665/605	6	152	180	19.6	14:1	115	4800	3600×1280×2150
HDYC440	440	YC6T600-D30	220	485/441	6	145	165	16.35	15:1	116	3800	3300×1200×2000
HDYC520	520	YC6T780-D30	220	572/520	6	145	165	16.35	15:1	116	4000	3200×1200×2050
HDYC56.	560	YC6TD840-D30	220	616/561	6	152	180	19.59	15.1	115	4600	3500×1250×2100
HDYC600	600	YC6TD900-D30	195	665/605	6	152	180	19.6	14:1	115	4800	3600×1280×2150
HDYC660	660	YC6TD1000-D30	195	735/668	6	152	180	19.6	14:1	115	4800	3600×1280×2150
HDYC680	680	YC6C102-D31	195	748/680	6	200	210	39.58	14.5:1	115	7500	3600×1300×2200
HDYC700	700	YC6C1070-D31	195	787/715	6	200	210	39.58	14.5:1	115	7500	3600×1300×2200
HDYC800	800	YC6C1220-D31	210	897/815	6	200	210	39.58	14.5:1	115	8000	3800×1300×2300
HDYC880	880	YC6C1320-D31	195	968/880	6	200	210	39.58	14.5:1	115	8000	3800×1300×2300

HDYC1000	1000	YC6C1520-D31	195	1118/1016	6	200	210	39.58	14.5:1	115	8800	4300×1550×2450
HDYC1100	1100	YC6C1660-D30	195	1221/1110	6	200	210	39.58	14.5:1	115	8800	4300×1550×2450
HDYC900	900	YC12VTD1350-D30	195	990/900	12V	200	210	79.17	14.5:1	124	12800	5100×2250×2650
HDYC1000	1000	YC12VTD1500-D30	195	1100/1000	12V	200	210	79.17	14.5:1	124	12800	5100×2250×2650
HDYC1120	1120	YC12VTD1680-D31	195	1230/1120	12V	200	210	79.17	14.5:1	124	12800	5100×2250×2650
HDYC1220	1220	YC12VTD1830-D30	195	1342/1220	12V	200	210	79.17	14.5:1	124	12800	5100×2250×2650
HDYC1300	1300	YC12VTD2000-D30	195	1480/1345	12V	200	210	79.17	14.5:1	124	12800	5100×2250×2650
HDYC1380	1380	YC12VC2070-D31	195	1520/1380	12V	200	210	79.17	14.5:1	124	13000	5100×2250×2650
HDYC1520	1520	YC12VC2270-D31	195	1607/1520	12V	200	210	79.17	14.5:1	124	13500	5200×2250×2650
HDYC1680	1680	YC12VC2510-D31	195	1850/1680	12V	200	210	79.17	14.5:1	124	14000	5300×2250×2650
HDYC1800	1800	YC12VC2700-D31	195	1985/1805	12V	200	210	79.17	14.5:1	124	14000	5300×2250×2650
HDYC2000	2000	YC12VC3000-D30	195	2206/2005	12V	200	210	79.17	14.5:1	124	14000	5300×2250×2650
HDYC1520	1520	YC16VTD2270-D30	198	1672/1520	16V	200	210	105.5	13.5:1	124	17000	6000*1800*2500
HDYC1650	1650	YC16VTD2470-D30	198	1815/1650	16V	200	210	105.5	13.5:1	124	17200	6100*1800*2500
HDYC1680	1680	YC16VTD2510-D30	198	1850/1680	16V	200	210	105.5	13.5:1	124	17200	6100*1800*2500
HDYC2000	2000	YC16VC3000-D31	202	2205/2005	16v	200	210	105.5	13.5:1	124	17300	6200*1800*2500
HDYC2200	2200	YC16VC3300-D31	201	2426/2205	16V	200	210	105.5	13.5:1	124	17400	6250*1800*2500
HDYC2400	2400	YC16VC3600-D31	199	2646/2405	16V	200	210	105.5	13.5:1	124	17500	6300*1800*2500

特殊型号规格定制：189-2253-7908