
不锈钢长型•金属球头/树脂球头▶ L尺寸选择加长型·金属球头/树脂球头▶

定位珠



型号		d	Н	L	V	S	负载(N)									
							超轻载		轻载		重载		超重载			
代码	М						min.	max.	min.	max.	min.	max.	min.	max.		
金属球头 ZAH51 ZAH52 ZAH53 ZAH54 树脂球头 ZAH71 ZAH72 ZAH73 ZAH74	4	2	0.8	15	1.5	2	0.5	1.72	1.8	5	3.8	9.9	2.5	12.5		
	5	2.5		18	2	2.5	1	3.31	3.2	9.9	4.8	19.7	11.2	24.1		
	6	3	1	20	2.5	3	1.6	5.06	5	15.4	9.7	29.5	17.7	33.4		
	8	5	2	23	2.5	4	2.4	6.66	5.4	19.2	12.6	39.3	21.4	45.3		
	10	6	2.5	27	3	5	3.1	8.1	8.8	24.2	18.5	49.1	23.5	60		
	12	8	3	32	3	6	3.4	9.9	10.4	29.4	19.5	58.9	24.1	63.7		
	16	10	4	40	3	8	6	15.7	14.8	49	29.3	98.1	43.6	116.3		

■ M3、M4前端部无扳手槽。仅为内六角孔安装。

! 负载min.表示初始负载,max.表示球头最大压入限度时的负载。

kgf=N×0.101972












○L尺寸选择加长型



型号			金属球头		树脂球头		V	S	负载(N)							
		L							超轻载型 ZAD01		轻载型 ZAD02/ZAD12		重载型 ZAD03		超重载型 ZAD04	
代码	М		d	Н	d	Н			min.	max.	min.	max.	min.	max.	min.	max.
金属球头 ZAD01 ZAD02 ZAD03 ZAD04	(3)	20 30	1.5	0.5	_	_	1	1.5	0.3	0.64	1	2	1.5	2.9	2.2	5
	4	20 30	2.5		2.4	0.7	1.5	2	0.6	1.6	2	4.9	3.9	9.8	2.5	12.6
	5	30 40	3	0.8	3	0.8	2	2.5	1	3.12	2.9	9.8	4.9	19.6	11.7	25.1
	6	30 40	3		3	0.8	2.5	3	1.6	4.85	4.9	14.7	9.8	29.4	18.7	35.3
	8	40 50	4	1	4	1	2.5	4	2.4	6.36	6.9	19.6	12.7	39.2	24.5	46.8
树脂球头- ZAD12	10	40 50	5	1.2	5	1.2	3	5	3	8.1	8.8	24.5	18.6	49	26.7	58.7
	12	50 60	7.1	1.8	7	1.8	3	6	3.5	9.68	9.8	29.4	19.6	58.8	26.1	62.3
	16	50 60	9.5	2.5	9.5	2.5	3	8	5.7	15.8	15.7	49	29.4	98	55.4	116

① 树脂球头无()内的规格。

! M3、M4前端部无扳手槽。仅为内六角孔安装。

! 负载min.表示初始负载,max.表示球头最大压入限度时的负载。











定导 位向 零零 件件 Α7

Kgf=N×0.101972