


NO.	TFT Pin Name	Function
1	VSS	Negative power supply, 0V
2	VDD	Power supply
3	WRX(SCL)	This pin is used serial interface clock. In 3-wire 9-bit / 4-wire 8-bit serial data interface.
4	SDA	serial data input/output bi-direction pin
5	RESET	This signal will reset the device and must be applied to properly initialize the chip.
6	D/C(RS)	4-line system (D/CX): Serves as command or parameter select. Data/Command Selection pin. Low: Command High: Parameter
7	BLK	Backlight switch button, low level backlight off
8	SDO	Serial output signal.

- NOTES:
1. DISPLAY TYPE: TFT 262 K COLOR, TRANSMISSIVE; NORMAL WHITE
 2. VIEWING DIRECTION : 12 O'CLOCK
 3. OPERATING TEMP: -20°C~70°C
 4. STORAGE TEMP: -30°C~80°C
 5. DRIVER IC: COG ST7796
 6. Backlight: 4 Chip White LEDs (PARALLEL)
 7. GENERAL TOLERANCE: ±0.3
 8. *为重点尺寸, Δ为修改记录
 9. 符合ROHS要求



HOT DISPLAY

Part Title: LCM-TFT035C1HVS4LN8D-V01

EDC No:

Unit: mm

Ver: A/0

Scale:

1:1

Tol: ±0.3

Drawn:

Checked:

Date: 2019-06-11